



 PRODUCT-DETAILS

AF16-30-10-13

AF16-30-10-13 100-250V50/60HZ-DC Contactor



General Information

Extended Product Type:	AF16-30-10-13
Product ID:	1SBL177001R1310
EAN:	3471523110632
Catalog Description:	AF16-30-10-13 100-250V50/60HZ-DC Contactor
Long Description:	The AF16-30-10-13 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 7.5 kW / 400 V AC (AC-3) or 10 hp / 480 V UL and switching power circuits up to 30 A (AC-1) or 30 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.
Display Name:	AF16-30-10-13

Ordering

Minimum Order Quantity:	1 piece
--------------------------------	---------

Customs Tariff Number: 85364900

Popular Downloads

EPLAN Data:	9AAC159647_EPLAN
Data Sheet, Technical Information:	1SBC100214C0202
Instructions and Manuals:	1SBC101027M6801
Instructions and Manuals (Part 2):	1SAC200017M0002
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	45 mm
Product Net Depth / Length:	77 mm
Product Net Height:	86 mm
Product Net Weight:	0.27 kg

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	0
Number of Poles:	3P
Standards:	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1
Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f):	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Rated Operational Current AC-1 (I_e):	(690 V) 40 °C 30 A (690 V) 60 °C 30 A (690 V) 70 °C 26 A
Rated Operational Current AC-3 (I_e):	(415 V) 60 °C 18 A (440 V) 60 °C 18 A (500 V) 60 °C 15 A (690 V) 60 °C 10.5 A (380 / 400 V) 60 °C 18 A (220 / 230 / 240 V) 60 °C 18 A
Rated Operational Current AC-3e (I_e):	(415 V) 60 °C 18 A (440 V) 60 °C 18 A (500 V) 60 °C 15 A (690 V) 60 °C 10.5 A (380 / 400 V) 60 °C 18 A (220 / 230 / 240 V) 60 °C 18 A

Rated Operational Current AC-15 (I_e):
 (500 V) 2 A
 (690 V) 2 A
 (24 / 127 V) 6 A
 (220 / 240 V) 4 A
 (400 / 440 V) 3 A

Rated Operational Current DC-1 (I_e):
 (110 V) 1-Pole, 40 °C 20 A
 (110 V) 1-Pole, 60 °C 20 A
 (110 V) 1-Pole, 70 °C 20 A
 (110 V) 2 Poles in Series, 40 °C 30 A
 (110 V) 2 Poles in Series, 60 °C 30 A
 (110 V) 2 Poles in Series, 70 °C 26 A
 (110 V) 3 Poles in Series, 40 °C 30 A
 (110 V) 3 Poles in Series, 60 °C 30 A
 (110 V) 3 Poles in Series, 70 °C 26 A
 (220 V) 2 Poles in Series, 40 °C 20 A
 (220 V) 2 Poles in Series, 60 °C 20 A
 (220 V) 2 Poles in Series, 70 °C 20 A
 (220 V) 3 Poles in Series, 40 °C 30 A
 (220 V) 3 Poles in Series, 60 °C 30 A
 (220 V) 3 Poles in Series, 70 °C 26 A
 (72 V) 1-Pole, 40 °C 30 A
 (72 V) 1-Pole, 60 °C 30 A
 (72 V) 1-Pole, 70 °C 26 A
 (72 V) 2 Poles in Series, 40 °C 30 A
 (72 V) 2 Poles in Series, 60 °C 30 A
 (72 V) 2 Poles in Series, 70 °C 26 A
 (72 V) 3 Poles in Series, 40 °C 30 A
 (72 V) 3 Poles in Series, 60 °C 30 A
 (72 V) 3 Poles in Series, 70 °C 26 A

Rated Operational Current DC-3 (I_e):
 (110 V) 1-Pole, 40 °C 8 A
 (110 V) 1-Pole, 60 °C 8 A
 (110 V) 1-Pole, 70 °C 8 A
 (110 V) 2 Poles in Series, 40 °C 30 A
 (110 V) 2 Poles in Series, 60 °C 30 A
 (110 V) 2 Poles in Series, 70 °C 26 A
 (110 V) 3 Poles in Series, 40 °C 30 A
 (110 V) 3 Poles in Series, 60 °C 30 A
 (110 V) 3 Poles in Series, 70 °C 26 A
 (220 V) 2 Poles in Series, 40 °C 8 A
 (220 V) 2 Poles in Series, 60 °C 8 A
 (220 V) 2 Poles in Series, 70 °C 8 A
 (220 V) 3 Poles in Series, 40 °C 30 A
 (220 V) 3 Poles in Series, 60 °C 30 A
 (220 V) 3 Poles in Series, 70 °C 26 A
 (72 V) 1-Pole, 40 °C 30 A
 (72 V) 1-Pole, 60 °C 30 A
 (72 V) 1-Pole, 70 °C 26 A
 (72 V) 2 Poles in Series, 40 °C 30 A
 (72 V) 2 Poles in Series, 60 °C 30 A
 (72 V) 2 Poles in Series, 70 °C 26 A
 (72 V) 3 Poles in Series, 40 °C 30 A
 (72 V) 3 Poles in Series, 60 °C 30 A
 (72 V) 3 Poles in Series, 70 °C 26 A

Rated Operational Current DC-5 (I_e):	(110 V) 1-Pole, 40 °C 4 A (110 V) 1-Pole, 60 °C 4 A (110 V) 1-Pole, 70 °C 4 A (110 V) 2 Poles in Series, 40 °C 20 A (110 V) 2 Poles in Series, 60 °C 20 A (110 V) 2 Poles in Series, 70 °C 20 A (110 V) 3 Poles in Series, 40 °C 30 A (110 V) 3 Poles in Series, 60 °C 30 A (110 V) 3 Poles in Series, 70 °C 26 A (220 V) 2 Poles in Series, 40 °C 4 A (220 V) 2 Poles in Series, 60 °C 4 A (220 V) 2 Poles in Series, 70 °C 4 A (220 V) 3 Poles in Series, 40 °C 16 A (220 V) 3 Poles in Series, 60 °C 16 A (220 V) 3 Poles in Series, 70 °C 16 A (72 V) 1-Pole, 40 °C 16 A (72 V) 1-Pole, 60 °C 16 A (72 V) 1-Pole, 70 °C 16 A (72 V) 2 Poles in Series, 40 °C 30 A (72 V) 2 Poles in Series, 60 °C 30 A (72 V) 2 Poles in Series, 70 °C 26 A (72 V) 3 Poles in Series, 40 °C 30 A (72 V) 3 Poles in Series, 60 °C 30 A (72 V) 3 Poles in Series, 70 °C 26 A
Rated Operational Current DC-13 (I_e):	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 (P_e):	(400 V) 7.5 kW (415 V) 9 kW (440 V) 9 kW (500 V) 9 kW (690 V) 9 kW (380 / 400 V) 7.5 kW (220 / 230 / 240 V) 4 kW
Rated Operational Power AC-3e (P_e):	(415 V) 9 kW (440 V) 9 kW (500 V) 9 kW (690 V) 9 kW (380 / 400 V) 7.5 kW (220 / 230 / 240 V) 4 kW
Rated Short-time Withstand Current Low Voltage (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 106 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Maximum Electrical Switching Frequency:	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour

Maximum Mechanical Switching Frequency:	3600 cycles per hour
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V
Power Loss:	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 1.2 W at Rated Operating Conditions AC-3 per Pole 0.35 W
Operate Time:	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied) :	2 x M4 Screws Placed Diagonally
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 0.75 ... 6 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 6 mm ²
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length:	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Tightening Torque:	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 1.5 N·m
Terminal Type:	Screw Terminals
Product Name:	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V
General Use Rating UL/CSA:	(600 V AC) 30 A
Horsepower Rating UL/CSA:	(120 V AC) Single Phase 1-1/2 hp (200 ... 208 V AC) Three Phase 5 hp (220 ... 240 V AC) Three Phase 5 hp (240 V AC) Single Phase 3 hp (440 ... 480 V AC) Three Phase 10 hp (550 ... 600 V AC) Three Phase 15 hp
Connecting Capacity Main Circuit UL/CSA:	Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA:	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG

Connecting Capacity Control Circuit UL/CSA:	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA:	Auxiliary Circuit 11 in-lb Control Circuit 11 in-lb Main Circuit 13 in-lb
Full Load Amps Motor Use:	(120 V AC) Single Phase 20 A (200 ... 208 V AC) Three Phase 17.5 A (220 ... 240 V AC) Three Phase 15.2 A (240 V AC) Single Phase 17 A (440 ... 480 V AC) Three Phase 14 A (550 ... 600 V AC) Three Phase 17 A

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand:	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible:	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27:	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g
Resistance to Vibrations:	4g Closed Position & 2g Open position 5 ... 300 Hz
Pollution Degree:	3

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP:	7a393deb-b5ee-452e-a4a0-02cb2786c00b China

Simplified SCIP:	5c4b3013-a234-44bc-8585-8ee74ca8bd1e Belgium 05b37de9-06b1-412b-b36a-40558952b2e6 Poland 83987f1c-85da-41fe-9bad-c3cbe6d08e2f Poland a08de364-3438-4693-97a4-1d42e0df4ae1 Norway 1cc03565-5a3b-4406-9a23-f53d0ed3d46b Netherlands 26bed53f-dc0f-4984-8b2e-28f613d6e5b5 Hungary 71630ddb-6d94-4716-a962-b7f5a42d8c78 Estonia aeafaa16-4dc1-482d-a2ed-c8a9a7857bc2 Finland e7f05330-47ca-4173-af56-34af52268aae Spain ec0d8073-a5f9-4e51-9d60-826b0bcefddeb Sweden 8f53cd22-04d3-4e82-9a06-f87dac1dce1f Germany 1abf1bec-ca4d-49d9-aa65-e2e88d858f6d Germany d17baa49-ac6b-4c8a-9677-cfbec4de6f46 Denmark 002365df-6444-4d0f-8a9e-170c9fb9399a Bulgaria 0db83908-6579-4d22-80a2-eaba40a8f67c Greece e92bd3e0-be38-4d8a-89d5-6dac683d678b Belgium 77f6c676-52c5-41e6-bc93-671ab47c6c2c Portugal 1985f3b2-717b-4f13-82f1-d0e9236eb2ff Germany 3098aa26-4b56-4300-ac27-1d7bfc8a371e Poland e5c4a693-1284-4bc5-bea2-c2cfad7658b1 France 84230eb2-0d00-4e71-ae6c-b1c655766493 Sweden 89d899a2-a08f-435d-8be3-6e50e8bf9e56 Germany b52b8bda-bb68-4f2a-a3b2-fa5a20c72fcd France 1ce8c6f4-b3d1-48da-8cc6-fd11f3dcb7f2 Hungary 2db7b5e9-1628-460d-be26-fd7abed141d Croatia 63885e47-d5ce-40f2-b0eb-db8ef3f9a996 Czech Republic b64fa0e6-48c7-4718-bc67-200a90ea6491 Germany
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill
EcoSolutions Profile:	1SBC100156C0308
End Of Life Disassembling Instructions:	1SBC101080M6801
Environmental Product Declaration - EPD:	1SBD250584E3000
Improved Energy Efficiency for Customers:	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 92.7 %

Certificates and Declarations

A2L Certificate – UL:	9AKK108469A4875 9AKK108469A4879
ABS Certificate:	ABS_20-2060694-PDA
BV Certificate:	BV_2634H24898C1
CB Certificate:	CB_SE-117714
CCC Certificate:	CCC_2024010304656669
CQC Certificate:	CQC2010010304445624 CQC2020010304298240

Declaration of Conformity - CCC:	2020980304001253 2020980304001082
Declaration of Conformity - CE:	1SBD250000U1000
Declaration of Conformity - UKCA:	1SBD250031U1000
DNV Certificate:	DNV_TAE00001AF-4
KC Certificate:	KC_HW02016-15005C
LR Certificate:	LRS_LR23403517TA-02
RINA Certificate:	RINA_ELE142224XG
RMRS Certificate:	RMRS_1802705280
UL Certificate:	UL-US-2150887-5 UL-CA-2142658-5
UL Listing Card:	E312527

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	87 mm
Package Level 1 Depth / Length:	79 mm
Package Level 1 Height:	47 mm
Package Level 1 Gross Weight:	0.27 kg
Package Level 1 EAN:	3471523110632

External Classifications and Standards

Object Classification Code:	Q
ETIM 7:	EC000066 - Power contactor, AC switching
ETIM 8:	EC000066 - Power contactor, AC switching
ETIM 9:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
IDEA Granular Category Code (IGCC):	4758 >> lec Contactors
E-Number (Finland):	3706243
E-Number (Sweden):	3211372

Accessories

Identifier	Description	Qty	Type	Unit Of Measure
1SBN010015R1001	CE5-01D0.1 Auxiliary Contact Block	1	CE5-01D0.1	piece
1SBN010015R1010	CE5-10D0.1 Auxiliary Contact Block	1	CE5-10D0.1	piece
1SBN010016R1001	CE5-01W0.1 Auxiliary Contact Block	1	CE5-01W0.1	piece

1SBN010016R1010	CE5-10W0.1 Auxiliary Contact Block	1	CE5-10W0.1	piece
1SBN010017R1001	CE5-01D2 Auxiliary Contact Block	1	CE5-01D2	piece
1SBN010017R1010	CE5-10D2 Auxiliary Contact Block	1	CE5-10D2	piece
1SBN010018R1001	CE5-01W2 Auxiliary Contact Block	1	CE5-01W2	piece
1SBN010018R1010	CE5-10W2 Auxiliary Contact Block	1	CE5-10W2	piece
1SBN010013R1010	CB5-10 Impulse Contact Block	1	CB5-10	piece
1SBN010013R1001	CB5-01 Impulse Contact Block	1	CB5-01	piece
1SBN010110R1010	CA4-10 Auxiliary Contact Block	1	CA4-10	piece
1SBN010110T1010	CA4-10-T Auxiliary Contact Block	1	CA4-10-T	piece
1SBN010110R1001	CA4-01 Auxiliary Contact Block	1	CA4-01	piece
1SBN010110T1001	CA4-01-T Auxiliary Contact Block	1	CA4-01-T	piece
1SBN010111R1010	CC4-10 Leading Auxiliary Contact Block	1	CC4-10	piece
1SBN010111R1001	CC4-01 Lagging Auxiliary Contact Block	1	CC4-01	piece
1SBN010120R1011	CAL4-11 Auxiliary Contact Block	1	CAL4-11	piece
1SBN010120T1011	CAL4-11-T Auxiliary Contact Block	1	CAL4-11-T	piece
1SBN010140R1022	CA4-22E Auxiliary Contact Block	1	CA4-22E	piece
1SBN010140R1031	CA4-31E Auxiliary Contact Block	1	CA4-31E	piece
1SBN010140R1040	CA4-40E Auxiliary Contact Block	1	CA4-40E	piece
1SBN010140R1004	CA4-04E Auxiliary Contact Block	1	CA4-04E	piece
1SBN010140R1322	CA4-22U Auxiliary Contact Block	1	CA4-22U	piece
1SBN010140R1122	CA4-22M Auxiliary Contact Block	1	CA4-22M	piece
1SBN010151R1011	CAT4-11E Auxiliary Contact / Coil Terminal Block	1	CAT4-11E	piece
1SBN010140R1331	CA4-31U Auxiliary Contact Block	1	CA4-31U	piece
1SBN010140R1131	CA4-31M Auxiliary Contact Block	1	CA4-31M	piece
1SBN010151R1111	CAT4-11M Auxiliary Contact / Coil Terminal Block	1	CAT4-11M	piece
1SBN010140R1340	CA4-40U Auxiliary Contact Block	1	CA4-40U	piece

1SBN010140R1113	CA4-13M Auxiliary Contact Block	1	CA4-13M	piece
1SBN010151R1311	CAT4-11U Auxiliary Contact / Coil Terminal Block	1	CAT4-11U	piece
1SBN070156T1000	LDC4 Additional Coil Terminal Block	1	LDC4	piece
1SBN030105T1000	VM4 Mechanical Interlock Unit	1	VM4	piece
1SBN081306T1000	BEA16-4 Connecting Link with Manual Motor Starter	1	BEA16-4	piece
1SBN010140R1104	CA4-04M Auxiliary Contact Block	1	CA4-04M	piece
1SBN030111R1000	VEM4 Mechanical and Electrical Interlock Set	1	VEM4	piece
1SBN020112R1000	TEF4-ON Frontal Electronic Timer	1	TEF4-ON	piece
1SBN020113R1000	TEF4S-ON Frontal Electronic Timer	1	TEF4S-ON	piece
1SBN010134R1011	CAL4-11K Auxiliary Contact Block	1	CAL4-11K	piece
1SBN020114R1000	TEF4-OFF Frontal Electronic Timer	1	TEF4-OFF	piece
1SBN081311R1000	BER16-4 Connection Set for Reversing Contactors	1	BER16-4	piece
1SBN020115R1000	TEF4S-OFF Frontal Electronic Timer	1	TEF4S-OFF	piece
1SBN081313R2000	BEY16-4 Connection Set for Star-Delta Starter	1	BEY16-4	piece
1SBN071303T1000	LY16-4 Connecting Strip	1	LY16-4	piece
1SBN071305R1000	LF16-4 Connecting Strip	1	LF16-4	piece
1SBN110108T1000	BX4 Protective Cover	1	BX4	piece
1SBN072304R1000	LH38-4 Connecting Strip	1	LH38-4	piece
1SBN071306R1000	LG16-4 Connecting Strip	1	LG16-4	piece
1SBN040100R1011	WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit	1	WA4-11	piece
1SBN040100R1014	WA4-14 250-500V50/60HZ-DC Mechanical Latching Unit	1	WA4-14	piece
1SBN110122T1000	BDT4 Test Block	1	BDT4	piece
1SBN040100R1010	WA4-10 24VDC Mechanical Latching Unit	1	WA4-10	piece
1SBN040100R1012	WA4-12 48-130V50/60HZ-DC Mechanical Latching Unit	1	WA4-12	piece
1SBN060100R1000	RA4 Interface Relay	1	RA4	piece
1SBN010146R1104	CA4-04MK Auxiliary Contact Block	1	CA4-04MK	piece
1SBN040100R1013	WA4-13 100-250V50/60HZ-DC Mechanical Latching Unit	1	WA4-13	piece

1SBN081322R1000	BER16-4KF Connection Set for Reversing Contactors	1	BER16-4KF	piece
1SBN010146R1113	CA4-13MK Auxiliary Contact Block	1	CA4-13MK	piece
1SBN081323R2000	BEY16-4KF Connection Set for Star-Delta Starter	1	BEY16-4KF	piece
1SBN070159T1000	LDC4K Additional Coil Terminal Block	1	LDC4K	piece
1SBN010160R1001	CA4-01K Auxiliary Contact Block	1	CA4-01K	piece
1SBN010146R1022	CA4-22EK Auxiliary Contact Block	1	CA4-22EK	piece
1SBN081314R1000	BEP16-30 Phase to phase connection	1	BEP16-30	piece
1SBN010160R1010	CA4-10K Auxiliary Contact Block	1	CA4-10K	piece
1SBN010146R1122	CA4-22MK Auxiliary Contact Block	1	CA4-22MK	piece
1SBN010160T1001	CA4-01K-T Auxiliary Contact Block	1	CA4-01K-T	piece
1SBN010160T1010	CA4-10K-T Auxiliary Contact Block	1	CA4-10K-T	piece
1SBN030113R1000	VEM4K Mechanical and Electrical Interlock Set	1	VEM4K	piece
1SBN010146R1031	CA4-31EK Auxiliary Contact Block	1	CA4-31EK	piece
1SBN010146R1131	CA4-31MK Auxiliary Contact Block	1	CA4-31MK	piece
1SBN010146R1040	CA4-40EK Auxiliary Contact Block	1	CA4-40EK	piece

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > AF Contactors > AF16

