

PRODUCT-DETAILS

T6S 800 PR221DS-LS/I In=800 3p F F

T6S 800 PR221DS-LS/I In=800 3p F F



Submitted by TECO Group

General Information

| | |
|-----------------------|---|
| Extended Product Type | T6S 800 PR221DS-LS/I In=800 3p F F |
| Product ID | 1SDA060278R1 |
| EAN | 8015644627409 |
| Catalog Description | T6S 800 PR221DS-LS/I In=800 3p F F |
| Long Description | C.BREAKER TMAX T6S 800 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 800 |

Ordering

| | |
|------------------------|---------------|
| E-Number (Finland) | 3655415 |
| EAN | 8015644627409 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 210 mm |
| Product Net Height | 268 mm |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight | 9 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 305 mm |
| Package Level 1 Height | 285 mm |
| Package Level 1 Depth / Length | 370 mm |
| Package Level 1 Gross Weight | 11 kg |
| Package Level 1 EAN | 8015644627409 |

Environmental

| | |
|-------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Additional Information

| | |
|---|--|
| Electrical Durability | 5000 cycle 60 cycles per hour |
| Mechanical Durability | 20000 cycle 120 cycles per hour |
| Number of Poles | 3 |
| Power Loss | at Rated Operating Conditions per Pole 32 W |
| Product Main Type | SACE Tmax T |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | CB |
| Rated Current (I_n) | Main Circuit 800 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 35 kA (690 V AC) 16.5 kA |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 1 s 10 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 35 kA (690 V AC) 22 kA |
| Rated Uninterrupted Current (I_u) | 800 A |
| Release | PR221DS-LS/I |
| Release Type | EL |
| Short-Circuit Performance Level | S |
| Standards | IEC |
| Sub-type | T6 |
| Suitable For | T6 |

| | |
|---------------------------------------|---------------------------------|
| Suitable for Product Class | Moulded Case Circuit Breakers |
| Terminal Connection Type | Fixed Circuit-Breakers Front |
| Test Voltage Max (U _{test}) | 3500 V |
| Version | F |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210015D0201 |
| Declaration of Conformity - CE | 1SDL000165R0006 |
| Environmental Information | 9AKK10103A1058 |
| Instructions and Manuals | 1SDH000511R0001 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

Classifications

| | |
|----------------------------|--|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| UNSPSC | 39121100 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

