

PRODUCT-DETAILS

A1C 125 TMF 50-500 1p F F

A1C 125 TMF 50-500 1p F F



General Information

Extended Product Type	A1C 125 TMF 50-500 1p F F
Product ID	1SDA066490R1
EAN	8015644692964
Catalog Description	A1C 125 TMF 50-500 1p F F
Long Description	C.BREAKER FORMULA A1C 125 FIXED SINGLE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 50-500 A

Ordering

EAN	8015644692964
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Order Code US and Canada	AAC050TW-1

Dimensions

Product Net Width	25.4 mm
Product Net Height	130 mm
Product Net Depth / Length	60 mm
Product Net Weight	0.25 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	143 mm
Package Level 1 Height	74 mm
Package Level 1 Depth / Length	93 mm
Package Level 1 Gross Weight	0.3 kg
Package Level 1 EAN	8015644692964

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Additional Information

Electrical Durability	1500 cycle
Mechanical Durability	Nr. Operations 8500 cycle
Number of Poles	1
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Power Loss	at Rated Operating Conditions per Pole 5.5 W
Product Main Type	SACE FORMULA
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 50 A
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	415 V AC 125 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 9 kA (380 V AC) 1.25 kA (415 V AC) 1.25 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 18 kA (380 V AC) 2.5 kA (415 V AC) 2.5 kA (125 V DC) 5 kA
Rated Uninterrupted Current (I_u)	125 A
Release	TMF
Release Type	TM
Short-Circuit Performance Level	C
Standards	IEC
Sub-type	A1
Terminal Connection Type	Front
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC210032D0204
Declaration of Conformity - CE	9AKK106713A5519
Environmental	1SDL000183R0001

Information	
Instructions and Manuals	1SDH000717R0002
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Formula DSA



Submitted by TECO Group