



PRODUCT-DETAILS

# A1C 125 TMF 100-1000 3p F F

## A1C 125 TMF 100-1000 3p F F



Submitted by TECO Group

| General Information   |   |
|-----------------------|---|
| Extended Product Type | A1C 125 TMF 100-1000 3p F F   |
| Product ID            | 1SDA066719R1  |
| EAN                   | 8015644694067   |
| Catalog Description   | A1C 125 TMF 100-1000 3p F F   |
| Long Description      | C.BREAKER FORMULA A1C 125 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 100-1000 A |

| Material Compliance                         |  |
|---|--|
| REACH Declaration                           | 9AKK108466A1425  |
| RoHS Declaration                            | 9AKK108466A1424  |
| RoHS Information                            | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326  |

## Environmental

|                           |                                    |
|---------------------------|------------------------------------|
| Environmental Information | 1SDL000183R0001<br>9AKK108467A6707 |
|---------------------------|------------------------------------|

## Ordering

|                          |               |
|--------------------------|---------------|
| Order Code US and Canada | AAC100TW      |
| EAN                      | 8015644694067 |
| Minimum Order Quantity   | 1 piece       |
| Customs Tariff Number    | 85362090      |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 76.2 mm |
| Product Net Height         | 130 mm  |
| Product Net Depth / Length | 60 mm   |
| Product Net Weight         | 0.79 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 136.5 mm      |
| Package Level 1 Height         | 124 mm        |
| Package Level 1 Depth / Length | 110.5 mm      |
| Package Level 1 Gross Weight   | 0.8 kg        |
| Package Level 1 EAN            | 8015644694067 |

## Additional Information

|                   |                              |
|-------------------|------------------------------|
| Product Main Type | SACE FORMULA                 |
| Product Name      | Moulded Case Circuit Breaker |
| Product Type      | Automatic Circuit Breaker    |
| Version           | F                            |

## Technical

|   |  |
|---|--|
| Electrical Durability                         | 1500 cycle                                 |
| Mechanical Durability                         | Nr. Operations 8500 cycle                  |
| Number of Poles                               | 3P   |
| Opening Time                                  | CB with SOR 15 ms<br>CB with UVR 15 ms     |
| Power Loss                                    | at Rated Operating Conditions per Pole 8 W |
| Rated Current ( $I_n$ )                       | Main Circuit 100 A                         |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ) | 6 kV                                       |
| Rated Insulation Voltage ( $U_i$ )            | 690 V                                      |
| Rated Operational                             | 550 V AC                                   |

|   |  |
|---|--|
| Voltage   | 250 V DC   |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (240 V AC) 15 kA<br>(380 V AC) 12.5 kA<br>(415 V AC) 6.25 kA<br>(440 V AC) 5 kA<br>(480 V AC) 4 kA<br>(500 V AC) 2.5 kA<br>(250 V DC) 2 Poles in Series 5 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (240 V AC) 30 kA<br>(380 V AC) 25 kA<br>(415 V AC) 25 kA<br>(440 V AC) 20 kA<br>(480 V AC) 15 kA<br>(500 V AC) 8 kA<br>(250 V DC) 10 kA                      |
| Rated Uninterrupted Current ( $I_u$ )                       | 125 A  |
| Release   | TMF  |
| Release Type  | TM   |
| Short-Circuit Performance Level                             | C  |
| Standards   | IEC  |
| Sub-type  | A1   |
| Terminal Connection Type                                    | Front  |

**Certificates and Declarations**

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210032D0204 |
| Declaration of Conformity - CE    | 9AKK106713A5519 |
| Wiring Diagram                    | 1SDM000067R0001 |
| Instructions and Manuals          | 1SDH000717R0001 |

**External Classifications and Standards**

|                            |  |
|----------------------------|--|
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 10                    | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q  |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                     | V11.1 : 27370409   |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Formula DSA



Submitted by TECO Group