

## PRODUCT-DETAILS

# XT1S 160 TMD 40-450 4p F F

# XT1S 160 TMD 40-450 4p F F



## General Information

|                       |                                                                                                        |
|-----------------------|--------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT1S 160 TMD 40-450 4p F F                                                                             |
| Product ID            | 1SDA080849R1                                                                                           |
| EAN                   | 8015644873776                                                                                          |
| Catalog Description   | XT1S 160 TMD 40-450 4p F F                                                                             |
| Long Description      | C.BREAKER TMAX XT1S 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 40-450 A |

## Ordering

|                          |                    |
|--------------------------|--------------------|
| EAN                      | 8015644873776      |
| Minimum Order Quantity   | 1 piece            |
| Customs Tariff Number    | 85362090           |
| Order Code US and Canada | XT1SE4040AFF000XXX |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 101.6 mm |
| Product Net Height         | 130 mm   |
| Product Net Depth / Length | 70 mm    |
| Product Net Weight         | 1.3 kg   |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 128 mm        |
| Package Level 1 Height         | 135 mm        |
| Package Level 1 Depth / Length | 143 mm        |
| Package Level 1 Gross Weight   | 1.4 kg        |
| Package Level 1 EAN            | 8015644873776 |

## Environmental

|             |                                                                        |
|-------------|------------------------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|------------------------------------------------------------------------|

## Additional Information

|                                                             |                                                                                                                                                                                                                                                                          |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Breaker Type to be Associated                       | Power Distribution                                                                                                                                                                                                                                                       |
| Current Type                                                | AC/DC                                                                                                                                                                                                                                                                    |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle                                                                                                                                                                                                                                        |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle                                                                                                                                                                                                         |
| Number of Poles                                             | 4                                                                                                                                                                                                                                                                        |
| Opening Time                                                | CB with SOR 15 ms<br>CB with UVR 15 ms                                                                                                                                                                                                                                   |
| Order Multiple                                              | 1 piece                                                                                                                                                                                                                                                                  |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                                                                                                                             |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                                                                                                             |
| Product Type                                                | CB                                                                                                                                                                                                                                                                       |
| Rated Current ( $I_n$ )                                     | 40 A                                                                                                                                                                                                                                                                     |
| Rated Voltage ( $U_r$ )                                     | 690 V                                                                                                                                                                                                                                                                    |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                                                                                                                     |
| Rated Instantaneous Short-Circuit Current Setting ( $I_i$ ) | 450 A                                                                                                                                                                                                                                                                    |
| Rated Insulation Voltage ( $U_i$ )                          | 800 V                                                                                                                                                                                                                                                                    |
| Rated Operational Voltage                                   | 690 V AC<br>500 V DC                                                                                                                                                                                                                                                     |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 63.75 kA<br>(230 V AC) 63.75 kA<br>(240 V AC) 63.75 kA<br>(380 V AC) 50 kA<br>(415 V AC) 37.5 kA<br>(440 V AC) 25 kA<br>(500 V AC) 18 kA<br>(525 V AC) 17.5 kA<br>(690 V AC) 5 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 3 Poles in Series 50 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(240 V AC) 85 kA<br>(380 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 50 kA<br>(500 V AC) 36 kA<br>(525 V AC) 35 kA<br>(690 V AC) 8 kA<br>(250 V DC) 2 Poles in Series 50 kA                                                    |

(500 V DC) 3 Poles in Series 50 kA

|                                       |                        |
|---------------------------------------|------------------------|
| Rated Uninterrupted Current ( $I_u$ ) | 160 A                  |
| Release                               | TMD                    |
| Release Type                          | TM                     |
| Setting Range                         | 28...40 A              |
| Short-Circuit Performance Level       | S                      |
| Standards                             | IEC                    |
| Sub-type                              | XT1                    |
| Terminal Connection Type              | Fixed Circuit-Breakers |
| Version                               | F                      |

### Certificates and Declarations (Document Number)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0206<br>1SDC210099D0206 |
| Declaration of Conformity - CE    | 9AKK106713A5532                    |
| Environmental Information         | 9AKK107991A8215                    |
| Instructions and Manuals          | 1SDH000719R0001                    |
| REACH Declaration                 | 9AKK108466A1425                    |
| RoHS Information                  | 9AKK108466A1424                    |

### Classifications

|               |                                                                              |
|---------------|------------------------------------------------------------------------------|
| ETIM 6        | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7        | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

### Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

