F204 AC-100/0.03 IEC 1/5



PRODUCT-DETAILS

F204 AC-100/0.03 IEC

Residual Current Circuit Breaker F200 - 4P - 30 mA - 100 A - Type AC



General Information		
Extended Product Type		F204 AC-100/0.03 IEC
Product ID		2CSF204005R1900
EAN	9	8012542936800
Catalog Description		Residual Current Circuit Breaker F200 - 4P - 30 mA - 100 A - Type AC
Long Description		ries assures protection to people and installations against fault current duct is manufactured according to international IEC standards, for the markets where it is required.

ABB EcoSolutions	
ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108469A3794
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 52.5 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging (wt. %)	Recycled Paper - 78 %
Extended Product Lifetime	Product Durability
End Of Life Disassembling	9AKK108468A4361

F204 AC-100/0.03 IEC 2/5

ì					
	Inst	rıı	ıct	ın	ns

Environmental Product	9AKK108467A3700
Doctoration EDD	

Technical	
Type of Residual Current	Type AC
Test Voltage (Ut)	170-254 \
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Poles	4F
Number of Modular Spacings per DIN Rail	4
Operating Characteristic	Instantaneous
Position of Neutral Terminals	Righ
Tightening Torque	2.8 N·m
Accessory Type	Auxiliary contact Auxiliary/Signal contact Shunt trip Undervoltage release Overvoltage release Motor Operating Device Bottom fitting auxiliary contact Autoreclosing Unit
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal Cage Terminal Failsafe Biconnect Fork Top/Bottom Failsafe Biconnect Fork Bottom
Options Provided	None
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm² Rigid 35 35 mm² Flexible 35 35 mm²
Rated Cross-Section	4 - Multi-Wired 035 mm ² 1 - Solid-Core 3535 mm ²
Wire Stripping Length	Top 12.7 mm Bottom 14.9 mm
Terminal Type	Screw Terminals
Electrical	
Rated Voltage (U _r)	230/400 V
Rated Operational Voltage	230 400 V AC
Rated Insulation Voltage (U _i)	500 V
Rated Impulse Withstand Voltage (U _{imp})	4 KV
Input Voltage Type	AC
Rated Current (I _n)	100 A
Rated Residual Current	30 mA
Rated Conditional Short- Circuit Current (I _{nc})	10 KA
Frequency (f)	50/60 Hz
Rated Frequency (f)	50 60 Hz
Power Loss	at Rated Operating Conditions per Pole 8.2 W Total 24.6 W

F204 AC-100/0.03 IEC 3/5

Design		
lumber of Modules	4	
A-t		
Material Compliance		
RoHS Declaration	9AKK106713A5602	
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
RoHS Date	20211115	
REACH Declaration	9AKK108467A9482	
REACH Information	True - contains substances > 0.1 mass percentage	
REACH Date Conflict Minerals	20240429 9AKK108468A3363	
Reporting Template	3ANN 100400A3303	
CMRT)		
SCIP	e8229506-bdcb-47ec-b10f-6ae72c1a19bf Italy	
NEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	
Environmental	<u> </u>	
Ambient Air Temperature	Operation -25 55 °C Storage -40 70 °C	
Degree of Protection	Storage -40 70 °C Terminals IP20	
Degree of Protection	Housing IP40	
Pollution Degree	2	
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 5 150 5 Hz	
Resistance to Shock acc.	25g 2 shocks 13 ms	
o IEC 60068-2-27		
Environmental Information	Refer to RoHS	
Dimensions		
<i>N</i> idth in Number of Modular Spacings	4	
Product Net Width	70 mm	
Product Net Height	85 mm	
Product Net Depth /	69 mm	
Length		
Product Net Weight	380 g	
Built-In Depth (t ₂)	69 mm	
Ordering		
Package Level 1 Units	box 1 piece	
Package Level 1 Gross	0.415 kg	
Veight		
One of the second of the secon	_	
Certificates and Declarations		
Declaration of Conformity CE	9AKK106713A5602	
nstallation		
nstructions and Manuals	9AKK107991A6127	
Mounting Type	DIN-Rail	
© 2025 ABB. All rights reserved.	2025/09/02 Subject to change wi	ithout no
S 2020 ADD. All lights reserved.	2020/03/02 Subject to Change Wi	iti lout 110t

F204 AC-100/0.03 IEC 4/5

Mounting Position Any

Popular Downloads	
Data Sheet, Technical Information	9AKK107991A8329

External Classifications and Standards	
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
ETIM 10	EC000003 - Residual current circuit breaker (RCCB)
eClass	V11.0 : 27142201
IDEA Granular Category Code (IGCC)	4875 >> Residual current circuit breaker (RCCB)
Object Classification Code	F
Standards	IEC 61008

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact 1CO	S2C-H6R	2	piece
2CDS200922R0001	S2C-S/H6R Universal Auxiliary/Signal Con	S2C-S/H6R	2	piece
2CDS200946R0001	S2C-H6-11R Auxiliary contact 1NO/1NC	S2C-H6-11R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary contact 2NC	S2C-H6-02R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary contact 2NO	S2C-H6-20R	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC Undervoltage release S	S2C-UA 24 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage release S	S2C-UA 24 AC	1	piece
2CSS200911R0008	S2C-UA 48 DC Undervoltage release S	S2C-UA 48 DC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage release	S2C-UA 400 AC	1	piece
2CSS200911R0001	S2C-UA 12 DC Undervoltage release S	S2C-UA 12 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC Undervoltage release	S2C-UA 230 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC Undervoltage release	S2C-UA 110 DC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage release S	S2C-UA 48 AC	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage release	S2C-OVP1	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage release	S2C-OVP2	1	piece
2CSF201998R0034	Autoreclosing unit F3C-AR	F3C-AR24	1	piece
2CSF202998R0034	Autoreclosing unit F3C-AR	F3C-AR230	1	piece
2CSS201998R0033	S3C-MOD24 Motor Operating Device	S3C-MOD24	1	piece
2CSS202998R0033	S3C-MOD230 Motor Operating Device	S3C-MOD230	1	piece

F204 AC-100/0.03 IEC 5/5

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \to\ Modular\ DIN\ Rail\ Products\ \to\ Residual\ Current\ Devices\ RCDs\ \to\ Residual\ Current\ Devices\ RCDs$









Glonitted by TECO Group