

PRODUCT-DETAILS

ACS580-01-062A-4

ACS580-01-062A-4 PN: 30 kW, IN: 62 A



Submitted by TECO Group

General Information

Global Commercial Alias	ACS580-01-062A-4
Product ID	3AUA0000080498
ABB Type Designation	ACS580-01-062A-4
EAN	6438177305545
Catalog Description	ACS580-01-062A-4 PN: 30 kW, IN: 62 A

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
Invoice Description	ACS580-01-062A-4 PN: 30 kW, IN: 62 A
Made To Order	No
Minimum Order Quantity	1 piece

Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	33.181 dm ³
--------------	------------------------

Dimensions

Product Net Weight	20 kg 44.092 lb
Product Net Depth / Length	257.00 mm 10.12 in
Product Net Height	636 mm 25.04 in
Product Net Width	203.00 mm 7.99 in
Package Level 1 Depth / Length	760.00 mm 31 in
Package Level 1 Height	428.00 mm 14 in
Package Level 1 Width	298.00 mm 11 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	1000 m 95
Sound dB (A)	69 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R4
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection

Submitted by TECO Group

Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use (I_{HD})	45 A
Output Current, Light-Overload Use (I_{LD})	58 A
Output Current, Normal Use (I_n)	62 A
Output Power, Heavy-Duty Use (P_{HD})	22.0 kW
Output Power, Light-Overload Use (P_{LD})	30 kW
Output Power, Normal Use (P_n)	30 kW
Apparent Power Output	43 kV·A
Efficiency Level	IE2
Standby Loss	19 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	247 W	90.2 %	0.6 %
0/50 %	322 W	93.2 %	0.7 %
0/100 %	574 W	93.8 %	1.3 %
50/25 %	270 W	94.6 %	0.6 %
50/50 %	370 W	96.1 %	0.9 %
50/100 %	683 W	96.4 %	1.6 %
90/50 %	430 W	97.5 %	1.0 %
90/100 %	873 W	97.4 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

Classifications

ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	596c7575-1ed1-48e9-be9a-d8fdd900606b Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive



Submitted by TECO Group