




---

 PRODUCT-DETAILS

## ACS480-04-033A-4

LV AC general purpose drive module, IEC: Pn  
15 kW, 32 A, 400 V (ACS480-04-033A-4)



Submitted by TECO Group

---

**General Information**

Global Commercial Alias	ACS480-04-033A-4
Product ID	3AXD50000199068
ABB Type Designation	ACS480-04-033A-4
EAN	6438177508403
Catalog Description	LV AC general purpose drive module, IEC: Pn 15 kW, 32 A, 400 V (ACS480-04-033A-4)
Long Description	<p>The ACS480 is a ready-made and capable package for many applications, such as compressors, fan and conveyors, in a variety of light industries, including food and beverage, logistics and warehousing, water and wastewater, and agriculture. It has all essential features built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance. It's a great fit for variable torque and basic speed applications, where you can leverage a compact, cabinet-optimized design for a cost-effective and efficient solution.</p>

---

**Ordering**

Country of Origin	China (CN) Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers)

and inductors.- Static converters

Invoice Description	ACS480-04-033A-4 PN: 15.0 kW, IN: 32 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

**Dimensions**

Product Net Weight	5.6 kg 12.346 lb
Product Net Depth / Length	213 mm 8.386 in
Product Net Height	240 mm 9.449 in
Product Net Width	262 mm 10.315 in
Package Level 1 Depth / Length	356 mm 14.016 in
Package Level 1 Height	275 mm 10.827 in
Package Level 1 Width	290 mm 11.417 in
Package Level 1 Units	1 carton

**Technical**

Number of Phases	3
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Sound dB (A)	69 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R4
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Module
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2

Submitted by TECO Group

Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use ( $I_{HD}$ )	25.0 A
Output Current, Light-Overload Use ( $I_{LD}$ )	30.5 A
Output Current, Normal Use ( $I_n$ )	32 A
Output Power, Heavy-Duty Use ( $P_{HD}$ )	11.0 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	15.0 kW
Output Power, Normal Use ( $P_n$ )	15 kW
Apparent Power Output	22 kV·A
Efficiency Level	IE2
Standby Loss	37 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	152 W	88.5 %	0.7 %
0/50 %	189 W	92.3 %	0.9 %
0/100 %	308 W	93.6 %	1.4 %
50/25 %	161 W	93.8 %	0.7 %
50/50 %	206 W	95.8 %	0.9 %
50/100 %	349 W	96.4 %	1.6 %
90/50 %	229 W	97.4 %	1.0 %
90/100 %	396 W	97.7 %	1.8 %

Temperature Rating Maximum 50 °C

### Technical UL

Output Current, Heavy-Duty Use (UL)	21.0 A
Output Current, Light-Overload Use (UL)	27.0 A
Output Current, Normal Use (UL)	27 A

### Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

### Environmental

SCIP	195df5c0-4685-425b-8b31-e03d5656a0e8 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

### Additional Information

---

Product Name

Frequency converter

---

---

### Categories

---

Drives → Low Voltage AC Drives → General Purpose Drives → ACS480-04 - Drive module



Submitted by TECO Group