



PRODUCT-DETAILS

3GBP111322-ADB

IE2 High Efficiency Cast Iron Motors, 4 kW,
400 V (3GBP111322-ADB)



General Information	
Product ID	3GBP111322-ADB
ABB Type Designation	M3BP 112MB 2
Catalog Description	IE2 High Efficiency Cast Iron Motors, 4 kW, 400 V (3GBP111322-ADB)

Ordering	
ABB Type Designation	M3BP 112MB 2
Invoice Description	M3BP 112MB 2
Product Name	3-Phase squirrel cage motor
Product Type	3BP2_M3BP_IE2_CI
Made To Order	No
Minimum Order Quantity	1 piece
Selling Unit of Measure	piece
Country of Origin	Spain (ES) Finland (FI) China (CN) Poland (PL)
Customs Tariff Number	85015220

Stocked At (Warehouses)	Menden, Germany
Medium Description	4kW, 2 Poles, Frame Size 112, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GBP111322-ADB)
Short Description	4kW, 2P, Frame Size 112, 3PH, 400V, 50Hz, IP55, IMB3/IM1001

Electrical

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	4.00 kW	2895 r/min	4.36 A	0.890	86.00 %	13.10 N·m	8.10
D	--	50 Hz	400 V	4.00 kW	2895 r/min	7.52 A	0.890	86.10 %	13.10 N·m	8.10
D	--	60 Hz	460 V	4.00 kW	3510 r/min	6.60 A	0.890	85.00 %	10.84 N·m	9.50
Connection Configuration	D									
Temperature Class Default	--									
Input Voltage (U _{in})	400 V									
Frequency (f)	50 Hz									
Output Power	4 kW									
Altitude	1000 m									
Ambient Temperature	40 °C									
IC Class	IC411									
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 86.0 % Partial Load (75%) 87.0 % Partial Load (50%) 86.5 %									
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 85.0 % Partial Load (75%) 84.4 % Partial Load (50%) 82.1 %									
IP Class	IP55									
Insulation Class	ICLF									
Direction of Rotation	Both sides									
Number of Poles (High)	2									
Two Speed Motor	No									
Type of Duty	S1									
Voltage Code	D									

Mechanical

Frame Material	Cast Iron
Frame Size	112
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Lubrication	For life
IM Class	IMB3 IM1001
Terminator Box Location	Top

Dimensions

Package Level 1 Units	1 carton
Product Net Depth / Length	403 mm
Product Net Height	259 mm
Product Net Width	230 mm
Product Net Weight	37 kg
Gross Weight	42 kg

Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
SCIP	54c45c7b-7581-40ab-b615-c1dc277d8a7 Finland (FI)

Classifications

Standards	IEC 60034-1
UNSPSC	26101100

Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Cast Iron Motors

