




---

 PRODUCT-DETAILS

## ACS150-03E-05A6-4

LV AC micro drive, IEC: Pn 2.2 kW, 5.6 A  
(ACS150-03E-05A6-4)



Submitted by TECO Group

---

### General Information

Global Commercial Alias	ACS150-03E-05A6-4
Product ID	68581796
ABB Type Designation	ACS150-03E-05A6-4
EAN	6410038079475
Catalog Description	LV AC micro drive, IEC: Pn 2.2 kW, 5.6 A (ACS150-03E-05A6-4)
Long Description	The ACS150 drives are designed to be incorporated into a wide variety of machines such as mixers, conveyors, fans or pumps. The ACS150 drives have an integrated user panel, potentiometer and a variety of features such as pre-defined connection macros, making drive selection and configuration easy. With an optional FlashDrop tool these drives can be configured quickly in volume.

---

### Ordering

Country of Origin	China (CN) Finland (FI)
Customs Tariff Number	85044085
Invoice Description	ACS150-03E-05A6-4 Pn 2,2kW, I2n 5,6A IP20
Made To Order	No
Minimum Order Quantity	1 piece

Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

### Dimensions

Product Net Weight	1.3 kg
Product Net Depth / Length	142 mm
Product Net Height	239 mm
Product Net Width	70 mm
Package Level 1 Depth / Length	350 mm
Package Level 1 Height	130 mm
Package Level 1 Width	220 mm
Package Level 1 Units	1 carton

### Technical

Number of Phases	3
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Multiple Battery Information	No battery / cell included
Frequency (f)	50/60 Hz
Frame Size	R1
Input Voltage ( $U_{in}$ )	380 ... 480 V
Mounting Type	Module for cabinet building
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 0 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	1
Analog Outputs	0
Number of Digital In/Outputs	5/0
Output Current, Light-Overload Use ( $I_{LD}$ )	5.6 A
Output Current, Normal Use ( $I_n$ )	5.6 A
Output Power, Light-Overload Use ( $P_{LD}$ )	2.2 kW
Output Power, Normal Use ( $P_n$ )	2.2 kW
Apparent Power Output	3.9 kV·A
Efficiency Level	IE2
Standby Loss	11 W

Submitted by TECO Group

Complete Drive Module  
 Efficiency (61800-9-2)

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	41 W	1.1 %	83.3 %
0 / 50 %	48 W	1.2 %	89.2 %
0 / 100 %	65 W	1.7 %	91.8 %
50 / 25 %	43 W	1.1 %	90.9 %
50 / 50 %	51 W	1.3 %	94.2 %
50 / 100 %	72 W	1.8 %	95.5 %
90 / 50 %	56 W	1.4 %	96.4 %
90 / 100 %	80 W	2.1 %	97.2 %

Temperature Rating Maximum 40 °C

**Classifications**

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

**Environmental**

SCIP	9bafda2d-8835-4ef6-a271-ddf6ea692d36 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

**Additional Information**

Product Name	Frequency converter
--------------	---------------------

Submitted by TEC Group

**Categories**

Drives → Low Voltage AC Drives → Micro Drives → ACS150 - Micro Drive



Submitted by TECO Group