



JG220U

IP66 40A 3P ISOLATOR

Technical Features

Architecture

| | |
|-----------------|----|
| Number of poles | 3 |
| Type of pole | 3P |

Electric current

| | |
|--|---------|
| Rated current | 40 A |
| Acceptable current rating AC21 | 40 A |
| Acceptable current rating AC21 category A | 40 A |
| Rated short-time withstand current Icw IEC 60947 | 0.48 kA |
| Acceptable current rating AC22 category A | 40 A |

Voltage

| | |
|------------------------------|-------------|
| Rated operational voltage Ue | 380 - 440 V |
|------------------------------|-------------|

Electric current

| | |
|---|------|
| Acceptable current rating AC23 category A | 40 A |
|---|------|

Voltage

| | |
|-----------------------------|-------|
| Rated insulation voltage Ui | 440 V |
|-----------------------------|-------|

Installation, mounting

| | |
|---------------------------|----------------|
| Nominal tightening torque | 2.50 - 2.50 Nm |
|---------------------------|----------------|

Dimensions

| | |
|--------|--------|
| Height | 170 mm |
| Width | 84 mm |
| Depth | 87 mm |

Safety

| | |
|-------------------------------|------|
| Ingress Protection (IP) class | IP66 |
|-------------------------------|------|

Power

| | |
|---|---------|
| Rated operational power under 400 V AC AC23 | 19800 W |
|---|---------|

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5 - 40 °C |
|-----------------------|------------|

Connection

| | |
|-------------------------------|------------------------|
| Cross-section rigid conductor | 6 - 10 mm ² |
|-------------------------------|------------------------|

Frequency

| | |
|-----------|------------|
| Frequency | 50 - 60 Hz |
|-----------|------------|

Sustainability

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|