



## Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	Compact NSX EasyPact CVS PowerPact Multistandard Compact NSX DC
Voltage release type	Undervoltage release
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz

## Complementary

Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Supply holding power	5 VA
Supply inrush power	10 VA
Mounting mode	Fixed
Response time	50 ms
Auxiliary connection terminal	Screw terminal 0... 1.5 mm <sup>2</sup>

## Packing Units

Package 1 Weight	127 g
Package 2 Weight	1.356 kg
Package 3 Weight	8.62 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------

Submitted by TECO Group