



Main

Device short name	MT400/630
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	Compact NSX400 Compact NSX630 Compact NSX400 DC PowerPact Multistandard circuit breaker Compact NSX630 DC EasyPact CVS400 circuit breaker PowerPact Multistandard EasyPact CVS630 circuit breaker EasyPact CVS400 PowerPact L circuit breaker EasyPact CVS630 PowerPact L
Control type	Standard
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz
Circuit breaker mounting mode	Fixed
Circuit breaker frame rated current	400 A 630 A

Complementary

Control signal type	Impulse Maintained
Response time	< 700 ms (opening) < 80 ms (closing)
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening

Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8
-----------------------------	----------------------------------------------------------

Packing Units

Package 1 Weight	3.15 kg
Package 2 Weight	19.924 kg
Package 3 Weight	90.616 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Submitted by TECO Group