Product datasheet

Specifications

Emergency luminaire, Exiway Light, Standard, selectable duration, 110lm, IP42, white

OVA44010

Main

Range	Exiway
Product name	Exiway Light
Product or component type	Emergency luminaire
Device application	Anti-panic lighting
Function	Standard
Operational mode	Maintained Non-maintained
Number of batteries	1 x 3.2 V 0.57 Ah LiFePO4
Colour tint	White
Light source	9 x LED 0.3 W
Visibility distance	20 m
Light source colour	Neutral
Wiring device additional information	2 wires connection

Complementary

Device mounting	Surface
Mounting support	Wall Ceiling
[Ue] rated operational voltage	230 V AC 50/60 Hz
Power consumption in VA	11.5 VA non-maintained 11.1 VA maintained
Power consumption in W	0.4 W non-maintained 0.8 W maintained
Electrical insulation class	Class II
LED lifespan	100000 h
Test function	Manual
Autonomy	1 h 1.5 h 2 h 3 h
Charging time	12 h
Luminous flux	Emergency condition: 110 lm for 1 h Emergency condition: 90 lm for 1.5 h Emergency condition: 70 lm for 2 h Emergency condition: 50 lm for 3 h Maintained mode: 70 lm
Local signalling	LED

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Submitted by TECO Group

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Material	Polycarbonate self-extinguishing
Height	112 mm
Depth	32 mm
Width	229 mm
Net weight	0.34 kg

Environment

IP degree of protection	IP42
IK degree of protection	IK09
fire resistance	850 °C
Product certifications	CE ENEC
Ambient air temperature for operation	0…40 °C
Standards	EN 60598-1: II EN 60598-2-22 EN 62471 UL 94 V2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	12.000 cm
Package 1 Length	23.500 cm
Package 1 Weight	384.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.306 kg

Contractual warranty

Warranty (in months)	18

Submitted by TECO Group

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**14 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**8 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**6 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**1 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

Recyclability potential, in %	**65**
End of life manual availability	End of Life Information
Removable battery	**Yes**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Submitted by TECO Group

Photometric Diagram



Submitted by TECO Group