

213.6333

PLUG
63A 2P+E 6h 200-250V 60Hz 50Hz
Mantle terminals



* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	PLUG

Description

The plug from the OPTIMA Series is designed for a rated voltage of 200-250V and a current of 63A. Featuring 2P+E poles and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With a protection degree of IP44/IP54, it offers reliable performance in various environments. The plug is equipped with mantle terminals and is compatible with straight type outlets. A version in black is also available by appending ".K" to the catalogue number. This product is engineered to meet the demands of professional applications, ensuring dependable functionality and versatility.

Mounting version	PORTABLE
------------------	----------

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [STP]
 Technical drawing [DWG]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--