

214.1633

PLUG
16A 2P+E 6h 200-250V 60Hz 50Hz
Screw terminals



* Product image may be indicative



**UK
CA**

EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	XENIA Series
Synthetical description	PLUG

Description

The plug from the XENIA Series is designed for a rated voltage of 200-250V and a current of 16A. Featuring 2P+E poles and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With a protection degree of IP44/IP54, it offers reliable performance in various environments. The plug is equipped with screw terminals and is compatible with straight type outlets. This product is engineered to meet the demands of professional applications, ensuring dependable functionality and durability.

Mounting version	PORTABLE
------------------	----------

TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz 50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND
Halogen free	HALOGEN FREE

DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[STP\]](#)
[Technical drawing \[DWG\]](#)