

318.3247

CONNECTOR

32A 3P+N+E 6h 346-415V 60Hz 50Hz
Screw terminals



* Product image may be indicative



EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	CONNECTOR
Description	
The OPTIMA Series connector is engineered for demanding electrical industrial environments, offering a rated voltage of 346-415V and a rated current of 32A. This connector features a 3P+N+E configuration and a 6h hour position, ensuring reliable performance across various applications. With an IP66/IP67/IP69 protection degree, it provides exceptional resistance to dust and water ingress. The connector is equipped with screw terminals for secure and efficient connections. Available in a straight outlet type, it is designed to meet the rigorous demands of industrial settings, ensuring durability and reliability.	
Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67/IP69
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]