

413.6367**FLUSH-MOUNTING SOCKET****63A 3P+N+E 6h 346-415V 50Hz 60Hz
100X110MM Mantle terminals**

* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA Series
Synthetical description	FLUSH-MOUNTING SOCKET

Description

The flush-mounting socket from the OPTIMA Series is engineered for robust electrical performance, supporting a rated voltage of 346-415V and a rated current of 63A. Designed with 3P+N+E poles and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. The socket offers a protection degree of IP44/IP54, ensuring reliable operation in various environments. Equipped with mantle terminals, it features angled outlets for optimal connectivity. A black version is available by appending ".K" to the catalogue number.

Mounting version	FLUSH MOUNTING
------------------	----------------

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	50Hz 60Hz
Terminals	Mantle terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	FLUSH MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)

■ DIMENSIONAL CHARACTERISTICS

Flange	100X110MM
--------	-----------

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Version also available in black; just add ".K" at the end of the catalogue number.
-----------------	--