

505.3283

INTERLOCKED SOCKET
32A 2P+E 6h 200-250V 60Hz 50Hz
136X125MM_PAR Screw terminals
With mechanical interlock



* Product image may be indicative



EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
EN IEC 60309-4 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OMNIA Series
Synthetical description	INTERLOCKED SOCKET
Description	
The OMNIA series interlocked socket is designed for surface mounting and features a 2P+E configuration. It operates at a rated voltage of 200-250V and a rated current of 32A, with a 6h hour position. Suitable for both 50Hz and 60Hz working frequencies, it offers robust protection with an IP66/IP67 rating. Constructed from durable thermoplastic material, this socket includes a mechanical interlock for enhanced safety. Engineered for industrial use, it ensures reliable performance in demanding environments. Note that this model does not include a fuse holder.	
Mounting version	SURFACE MOUNTING

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz 50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Contact material	CuZn (brass)
Padlock	ø4,7mm

DIMENSIONAL CHARACTERISTICS

Flange	136X125MM_PAR
--------	---------------

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]
Instruction manual

OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER
Catalogue notes	Blank side with drilling point marks
	Note: in case of mounting with ADVANCE2 System, use METRIC drilling point mark.