

505.3286**INTERLOCKED SOCKET**

32A 3P+E 6h 380-415V 60Hz 50Hz

136X125MM_PAR Screw terminals

With mechanical interlock



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

EN IEC 60309-4 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OMNIA Series
Synthetical description	INTERLOCKED SOCKET
Description	The OMNIA series interlocked socket is designed for surface mounting in industrial settings. It operates at a rated voltage of 380-415V and a rated current of 32A, with a 3P+E configuration and a 6h hour position. Compatible with both 50Hz and 60Hz working frequencies, it provides robust protection with an IP66/IP67 rating. Constructed from durable thermoplastic material, this socket includes a mechanical interlock for enhanced safety. Notably, it is designed without a fuse holder, ensuring streamlined functionality. Engineered for demanding environments, it guarantees reliable performance and safety in industrial applications.
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Contact material	CuZn (brass)
Padlock	ø4,7mm

■ DIMENSIONAL CHARACTERISTICS

Flange	136X125MM_PAR
--------	---------------

■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER
Catalogue notes	Blank side with drilling point marks
	Note: in case of mounting with ADVANCE2 System, use METRIC drilling point mark.