

505.6387**INTERLOCKED SOCKET**

63A 3P+N+E 6h 346-415V 60Hz 50Hz
136X275MM_PAR Screw terminals
With mechanical interlock



* Product image may be indicative



EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
EN IEC 60309-4 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OMNIA Series
Synthetical description	INTERLOCKED SOCKET

Description

The OMNIA series interlocked socket is designed for surface mounting in industrial settings. It features a 3P+N+E configuration and operates at a rated current of 63A with a rated voltage of 346-415V. The socket is compatible with both 50Hz and 60Hz working frequencies and is set at a 6h hour position. It offers robust protection with an IP66/IP67 rating and includes a mechanical interlock for enhanced safety. Constructed from durable thermoplastic material, this socket is engineered to deliver reliable performance in demanding environments. Note that this model does not include a fuse holder.

Mounting version	SURFACE MOUNTING
------------------	------------------

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Watertight
Protection degree IP	IP66/IP67
Protection degree IK	IK08
Contact material	CuZn (brass)
Padlock	ø4,7mm

■ DIMENSIONAL CHARACTERISTICS

Flange	136X275MM_PAR
--------	---------------

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[STP\]](#)
[Technical drawing \[DWG\]](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
Notes	WITHOUT FUSE HOLDER
Catalogue notes	Blank side with drilling point marks
	Note: in case of mounting with ADVANCE2 System, use METRIC drilling point mark.