

513.1657T**SURFACE MOUNTING SOCKET****16A 3P+N+E 6h 346-415V 60Hz 50Hz****Screw terminals**

* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET

Description

The OPTIMA-TOP Series surface mounting socket is engineered for robust industrial applications. Featuring an angled outlet design, it accommodates a 3P+N+E configuration with a rated current of 16A and supports working frequencies of 50Hz and 60Hz. The socket operates within a rated voltage range of 346-415V and is designed with a 6h hour position. It offers an IP44 protection degree, ensuring resistance to dust and splashing water. The socket is equipped with screw terminals for secure connections. Additional features include a rubber threaded cable sleeve and a threaded break-through knock out, enhancing its versatility and ease of installation.

Mounting version	SURFACE MOUNTING
------------------	------------------

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M25X1,5

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [STP]
 Technical drawing [DWG]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Rubber threaded cable sleeve included
	Threaded break-through knock out