

513.3256T

SURFACE MOUNTING SOCKET
32A 3P+E 6h 380-415V 60Hz 50Hz
Screw terminals



* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET

Description

The OPTIMA-TOP Series surface mounting socket is engineered for robust industrial applications. Featuring an angled outlet with a 3P+E configuration, it supports a rated current of 32A and operates efficiently at both 50Hz and 60Hz frequencies. Designed for a rated voltage of 380-415V, it is equipped with a 6h hour position and offers an IP44 protection degree, ensuring reliable performance in demanding environments. The socket includes screw terminals for secure connections and comes with a rubber threaded cable sleeve and a threaded break-through knock out, enhancing its versatility and ease of installation.

Mounting version	SURFACE MOUNTING
------------------	------------------

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M32X1,5

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [STP]
 Technical drawing [DWG]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Rubber threaded cable sleeve included
	Threaded break-through knock out