

513.6353T

SURFACE MOUNTING SOCKET
63A 2P+E 6h 200-250V 60Hz 50Hz
Mantle terminals



* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET

Description

The OPTIMA-TOP Series surface mounting socket is engineered for robust industrial applications. Featuring an angled outlet design, it accommodates a 2P+E configuration with a rated current of 63A. It operates efficiently within a working frequency range of 50Hz to 60Hz and supports a rated voltage of 200-250V. The socket is designed with a 6h hour position and offers a protection degree of IP44/IP54, ensuring reliable performance in demanding environments. Equipped with mantle terminals, it includes a cable gland, open threaded cable entry, and a threaded cap/cable sleeve for secure and efficient installation.

Mounting version	SURFACE MOUNTING
------------------	------------------

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	BLUE
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M40X1,5

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [STP]
 Technical drawing [DWG]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Cable gland included
	Threaded cap/cable sleeve included