

513.6356T

SURFACE MOUNTING SOCKET
63A 3P+E 6h 380-415V 60Hz 50Hz
Mantle terminals



* Product image may be indicative



EN IEC 60309-1 (2022)

EN IEC 60309-2 (2022)

Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET

Description

Introducing the OPTIMA-TOP Series surface mounting socket, designed for robust industrial applications. This socket features an angled outlet configuration with 3P+E poles, supporting a rated current of 63A and operating at frequencies of 50Hz and 60Hz. It accommodates a rated voltage range of 380-415V and is positioned at 6h. The socket offers a protection degree of IP44/IP54, ensuring reliable performance in demanding environments. Equipped with mantle terminals, it includes a cable gland, open threaded cable entry, and a threaded cap/cable sleeve for secure and efficient installation. This product is engineered to meet the rigorous demands of industrial electrical systems.

Mounting version	SURFACE MOUNTING
------------------	------------------

TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+E
Hour position	6h
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Mantle terminals

PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	ANGLED
Contact material	CuZn (brass)
Cable entry	M40X1,5

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]

OPTIONS & VARIOUS NOTES

Catalogue notes	Open threaded cable entry
	Cable gland included
	Threaded cap/cable sleeve included