

590.GE3212**SWITCH DISCONNECTOR**

32A 2P IP66/IP69 110x150x87mm Y1
IK09 GENERAL GREY/BLACK GW
650°C



* Product image may be indicative



EN IEC 60947-3 (2021)

EN IEC 60947-1 (2021)

Low voltage direct. 2014/35/EU

DIRECTIVE RoHS 2011/65/EU

■ GENERAL CHARACTERISTICS

Commercial Series	ISOLATORS-TP Series
Synthetical description	SWITCH DISCONNECTOR

Description

The switch disconnectors-tp series is engineered for industrial applications, featuring a durable construction of engineering plastic. With a handle of grey/black, this device is designed for surface mounting. It carries a rated current of 32A and operates efficiently at 32A in AC23A (415V). The switch disconnectors offers a high protection degree of IP66/IP69 and an impact resistance of IK09, ensuring resilience in demanding environments. Configured with 2P poles and a Y1 switch size, it operates at a rated voltage of 690V. Notable features include a blank side with drilling point marks, break-through cable entries, a reversible base, and a door interlock. The handle is padlockable in both OFF (up to three padlocks) and ON (one padlock) positions.

Type	GENERAL
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	2P
Switch size	Y1
Rated voltage	690V
Rated insulation voltage (Ui)	690VAC
Rated impulse voltage (Uimp)	4kV
Thermal current (Ithe)	40A
Current (Ie) in AC21A (415V)	40A
Current (Ie) in AC21A (500V)	32A
Current (Ie) in AC21A (690V)	32A
Current (Ie) in AC22A (415V)	32A
Current (Ie) in AC22A (500V)	32A
Current (Ie) in AC22A (690V)	32A
Current (Ie) in AC23A (415V)	32A
Current (Ie) in AC23A (500V)	25A
Current (Ie) in AC23A (690V)	25A
Current (Ie) in AC3 (415V)	25A
Current (Ie) in AC3 (690V)	18A
Current (Ie) in DC22A (250V)	32A
Current (Ie) in DC22A (600V)	10A
Power AC23A (415V)	15kW
Short-time withstand current	400A Icw(1s)
Conditional short circuit cur.	10kAeff
Associate fuse - type gG	32A
Terminals - Flexible wires	1.5-10mm ²
Terminals - Rigid wires	1.5-16mm ²

■ PHYSICAL CHARACTERISTICS

Construction type	Enclosed
Mounting version	SURFACE MOUNTING
Material	ENGINEERING PLASTIC
Protection degree IP	IP66/IP69
Installation temperature	-25°C/+60°C
Colour	GREY/BLACK
GLOW WIRE	GW 650°C
Protection degree IK	IK09

Padlock	ø6mm
Terminals tightening torque	0,8Nm

■ DIMENSIONAL CHARACTERISTICS

Dimensions	110x150x87mm
------------	--------------

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Handle padlockable in OFF (3 padlocks) and ON (1 padlock) position
	Equipped with door interlock
	Reversible base
	Blank side with drilling point marks on top side base
	Break-through cable entries on bottom side base

Submitted by TECO Group