

590.YM67B2

FRONT OPERATOR PADLOCKABLE
IP65 standard 67x67mm Y1 F1 D1
GENERAL GREY/BLACK



* Product image may be indicative



CSA C22.2 No. 60947-4-1-14
 EN IEC 60947-3 (2021)
 EN IEC 60947-1 (2021)
 CSA C22.2 No. 60947-1-13
 UL 60947-4-1
 UL 60947-1
 UL 486A

Low voltage direct. 2014/35/EU

■ GENERAL CHARACTERISTICS

Commercial Series	COMMAND Series
Synthetical description	FRONT OPERATOR PADLOCKABLE
Type	GENERAL
Mounting version	B

■ TECHNICAL CHARACTERISTICS

Switch size	Y1
	F1
	D1
Rated voltage	690V

■ PHYSICAL CHARACTERISTICS

Mounting version	B
Material	THERMOPLASTIC
Protection degree IP	IP65
Protection degree UL	TYPE 1, 4, 4X
Installation temperature	-25°C/+60°C
Colour	GREY/BLACK
Padlock	ø6mm

■ DIMENSIONAL CHARACTERISTICS

Diameter	standard
Dimensions	67x67mm
Flange	67X67MM

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [STP]
 Technical drawing [DWG]

■ OPTIONS & VARIOUS NOTES

Catalogue notes	Shaft not included (to buy separately)
	Handle padlockable in OFF position only (3 padlocks)
	For general use and emergency switches.
	For base mounting version with door interlock (B)